

# TECHNICAL DATA SHARK FLAT EMULSION 900

**DESCRIPTION**: Shark FLAT EMULSION 900 is a highly durable, water-based with a silky touch finish that comes with excellent coverage and opacity.

**KEY FEATURES**:

- FLAT Finish
- Environment Friendly
- Excellent Durability
- High Opacity
- Easy Clean Up

### **RECOMMENDED FOR**

- interior & exterior use on new or previously painted wallboard, plaster, masonry.
- The product has high covering power and excellent transpiration.
- One desire a highly washable finish

## **TYPICAL PROPERTIES:**

| Type of paint                                  |        | Water born                                    |
|--|--------|---|
| color  |        | Off white colors and other in catalogue       |
| Dilute with                                    |        | Water   |
| DILUTION %                                     |        | 25 - 30%                                      |
| Density  |        | 1.446 g/ml                                    |
| Consistency                                    |        | WITH ALL TYPE OF CONCRET                      |
| Scrub Resistance                               |        | 890 cycles/ BDG 256 wet abrasion scrub tester |
| Gloss Level                                    |        | 0.3 U.G                                       |
| Packaging                                      | Pail   | 17 liter                                      |
|  | Gallon | 3.8 L   |
| Clean Up                                       |        | Soap and water                                |
| Coverage                                       |        | 15.17 m <sup>2</sup> / 1L/ 30 mic / 1 coat    |
| Dry Times<br>25°C and 50% Relative<br>Humidity | Touch  | 2 hours                                       |
|  | Recoat | 6 hours                                       |
| Storage  |        | Protect from freezing.                        |

#### **INSTRUCTIONS FOR USE:**

- SURFACE PREPARATION:
- a) Brush over the surface well
- b) An undercoat of Shark primer Emulsion based thinned 1: 0.3 of pure water

On old plasters which are chalky, absorbent and degraded:

a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.





**b)** An undercoat of Shark primer Enamel based thinned 1: 0.5 white spirit N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

## METHOD OF APPLICATION:

- After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:
- a) A first coat flat emulsion 900 thinned with about 35% of water.
- b) A second coat flat emulsion 900 thinned with about 20% of water.

N.B. The product may also be applied by spray even airless type sprayer.

CAUTION: Keep from freezing. Avoid prolonged contact with skin or breathing spray mist. Do not take internally. Close container after each use. Use with adequate ventilation

. IMPORTANT: Spray equipment must be operated in strict accordance with manufacturer's instructions. When spray applying, wear spray mask, eye protection and protective clothing. FIRST AID: In case of skin contact, wipe area clean with cloth and wash thoroughly with soap and water; for eyes, flush with water for 15 minutes and get medical attention. If swallowed, get medical attention immediately. KEEP OUTOF REACH OF CHILDREN.

