

TECHNICAL DATA SHARK GLOSS EMULSION 1200

<u>DESCRIPTION</u>: Shark GLOSS EMULSION 1200 is a highly durable, water-based with a silky touch finish that comes with excellent coverage and opacity.

KEY FEATURES:

- Gloss Finish
- Environment Friendly
- Excellent Durability
- High Opacity
- Easy Clean Up

RECOMMENDED FOR

- interior & exterior use on new or previously painted wallboard, plaster, masonry.
- The product has high covering power and excellent transpiration.
- · One desire a highly washable finish

TYPICAL PROPERTIES:

Type of paint		Water born
color		Off white colors and other in catalogue
Dilute with		Water
DILUTION %		25 -30%
Density		1.18 g/ml
Consistency		WITH ALL TYPE OF CONCRET
Scrub Resistance		1950 Cycles / BDG 256 wet abrasion scrub tester
Gloss Level		75.9 U.G
Packaging	Pail	17 liter
	Gallon	3.8 L
Clean Up		Soap and water
Coverage		15.6 m² / 1L/ 30 mic / 1 coat
Dry Times 25°C and 50% Relative Humidity	Touch	2 hours
	Recoat	6 hours
Storage		Protect from freezing.

INSTRUCTIONS FOR USE:

- SURFACE PREPARATION:
- a) Brush over the surface well
- b) An undercoat of Shark primer Emulsion based thinned 1: 0.3 of pure water

On old plasters which are chalky, absorbent and degraded:

a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.







Shark Paints Chemicals

www.sharkpaints.com

b) An undercoat of Shark primer Enamel based thinned 1: 0.5 white spirit N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

METHOD OF APPLICATION:

- After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:
- a) A first coat gloss emulsion 1200 thinned with about 35% of water.
- b) A second coat gloss emulsion 1200 thinned with about 20% of water.
- N.B. The product may also be applied by spray even airless type sprayer.

CAUTION: Keep from freezing. Avoid prolonged contact with skin or breathing spray mist. Do not take internally. Close container after each use. Use with adequate ventilation

. IMPORTANT: Spray equipment must be operated in strict accordance with manufacturer's instructions. When spray applying, wear spray mask, eye protection and protective clothing. FIRST AID: In case of skin contact, wipe area clean with cloth and wash thoroughly with soap and water; for eyes, flush with water for 15 minutes and get medical attention. If swallowed, get medical attention immediately. KEEP OUTOF REACH OF CHILDREN.



