



TECHNICAL DATA

SHARK SATIN-SHEEN EMULSION 1100

DESCRIPTION: Shark SATIN-SHEEN EMULSION 1100 is a highly durable, water-based with a silky touch finish that comes with excellent coverage and opacity.

KEY FEATURES:

- Satin-Sheen Finish
- Environment Friendly
- Excellent Durability
- High Opacity
- Easy Clean Up

RECOMMENDED FOR

- interior & exterior use on new or previously painted wallboard, plaster, masonry.
- The product has high covering power and excellent transpiration.
- One desire a highly washable finish

TYPICAL PROPERTIES:

Type of paint	Water born	
color	Off white colors and other in catalogue	
Dilute with	Water	
DILUTION %	25 -30%	
Density	1.36 g/ml	
Consistency	WITH ALL TYPE OF CONCRET	
Scrub Resistance	1000 Cycles / BDG 256 wet abrasion scrub tester	
Gloss Level	3 U.G	
Packaging	Pail	17 liter
	Gallon	3.8 L
Clean Up	Soap and water	
Coverage	15.35 m ² / 1L/ 30 mic / 1 coat	
Dry Times 25°C and 50% Relative Humidity	Touch	2 hours
	Recoat	6 hours
Storage	Protect from freezing.	

INSTRUCTIONS FOR USE:

- SURFACE PREPARATION:
 - a) Brush over the surface well
 - b) An undercoat of Shark primer Emulsion based thinned 1: 0.3 of pure water

On old plasters which are chalky, absorbent and degraded:

- a) carefully remove all parts which are not securely anchored to the background and restore the surface where necessary.





b) An undercoat of Shark primer Enamel based thinned 1: 0.5 white spirit
N.B. In every case however, before the application, the substrate should be dry, clean of any traces of grease or from -oils and any parts not perfectly anchored to the background.

METHOD OF APPLICATION:

- After an adequate preparation of the substrate, according to the above indications, apply the product by the brush or roller as follows:
 - a) A first coat SATIN-SHEEN EMULSION 1100 thinned with about 35% of water.
 - b) A second coat SATIN-SHEEN EMULSION 1100 thinned with about 20% of water.N.B. The product may also be applied by spray even airless type sprayer.

CAUTION: Keep from freezing. Avoid prolonged contact with skin or breathing spray mist. Do not take internally. Close container after each use. Use with adequate ventilation

. IMPORTANT: Spray equipment must be operated in strict accordance with manufacturer's instructions. When spray applying, wear spray mask, eye protection and protective clothing. FIRST AID: In case of skin contact, wipe area clean with cloth and wash thoroughly with soap and water; for eyes, flush with water for 15 minutes and get medical attention. If swallowed, get medical attention immediately. KEEP OUTOF REACH OF CHILDREN.

